



SAFETY DATASHEET

1. Identification of the substance/preparation and of the company/undertaking

Contact Adhesive 281

Date of issue: 05-12-08
Replaces (previous issues): 05-09-06

Product codes:
-

Company: Dana Lim A/S, Københavnsvej 220,
DK-4600 Køge, Denmark
Ph.: (+45) 56 64 00 70 Fax: (+45) 56 64 00 90
E-mail: info@danalim.dk

Emergency phone number:
+45 35 31 60 60 / +45 35 31 35 31

Type: Solvent based adhesive.

Intended use:
Contact adhesive. For technical information, see Product information

2. Hazards identification:



Harmful by inhalation and in contact with skin. Irritating to eyes and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

3. Composition/information on ingredients:

Classification according to Danish / EC legislation:

Name:	Conc.:	Symbol:	R-phrases*:
Xylene EINECS-nr. 215-535-7 CAS-nr. 1330-20-7	<30 %	Xn	R10-20/21-38
Ethyl acetate EINECS-nr. 205-500-4 CAS-nr. 141-78-6	< 30 %	F, Xi	R11-36-66-67
Naphtha (petroleum), hydrotreated light (<0,1% benzene) EINECS-nr. 265-151-9 CAS-nr. 64742-49-0	<25 %	F, Xn, N	R11-38-51/53-65-67
Zink oxide EINECS-nr. 215-222-5 CAS-nr. 1314-13-2	<1%	N	R50/53
Colophony EINECS-nr. 232-475-7 CAS-nr. 8050-09-7	<0,5 %	Xi	R43

*For full text see Section 16.

4. First aid measures:

General:

In all cases of doubt, seek medical attention.

Inhalation:

Remove affected person from area. Provide fresh air and rest. If breathing has stopped, administer artificial respiration. Give nothing to mouth. If unconscious, place in the recovery position and seek medical advice.

Eye contact:

Remove contact lenses. After separating the eyelids flush with copious amounts of water, at least 15 min. Seek medical advice.

Skin contact:

Remove contaminated clothing. Thoroughly wash affected skin with soap and plenty of water. Do not use solvents or thinners. Consult a physician in case skin irritation persists.

Ingestion:

Rinse out mouth with water, drink plenty of water. Do not induce vomiting. Seek immediate medical advice.

Burn:

Rinse with cold water until the pain stops. During rinsing remove clothes which are not burned unto the skin. If medical advice is necessary, rinse until doctor takes over treatment.

5. Fire fighting measures:

Suitable extinguishing media: Carbon dioxide-, foam-extinguisher, water spray.
Do not use water jet, which spread the fire.

Fire can produce dense black smoke containing hazardous products. Exposure to decomposition products may be a hazard to health. Appropriate self-containing breathing apparatus and approved protecting clothing are required.

Cool packagings exposed to the fire with water spray.

6. Accidental release measures:

Exclude sources of ignition and ventilate the area. Avoid breathing the vapours. See protective measures listed in section 8.

In case of spills cover product with an inert adsorbent (e.g. sand, soil, granulate) and place into marked containers. Hold waste for dispose according to local regulations (see section 13).

Clean preferably with a detergent, avoid the use of solvents.

Do not allow to enter drains or water courses.

If the product enters drains or sewers the local water company should be contacted immediately.

7. Handling and storage:**Handling:**

Provide good room ventilation.

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentrations higher than the occupational exposure limits.

The product should only be used in areas from which all-naked lights and other sources of ignition have been excluded.

Electrical equipment should be protected to the appropriate standard.

The product may charge electrostatically. Operators should wear anti-static footwear. Non-sparking tools should be used.

Avoid skin and eye contact. Avoid inhalation of vapour and spray mist. Smoking, eating and drinking should be prohibited in areas of storage and use.

For personal protection, see section 8.

Storage:

Follow the technical requirements of storage of Highly Flammable Liquids.

Do not store product in direct neighbourhood of food, drinks and animal feed.

Store product out of the reach of children in tightly closed tubes in a dry, well-ventilated area.

Keep the product away from sources of ignition, oxidizing agents and strongly alkaline or acidic materials.

No smoking. Prevent unauthorised access. Keep in a cool place - protect from heat.

8. Exposure controls / personal protection:**Technical facility design:**

All work shall be arranged so that inhalation of vapours and also smudge of the skin is reduced to a minimum.

Provide adequate ventilation. Where reasonable practice this should be achieved by the use of local exhaust ventilation and good general extraction.

Occupational exposure limits:

Name:	ppm	mg/m ³
Xylene	25	108
Ethylacetat	150	540
Heptane	200	820

The list was valid during the compilation (Danish list, August 2007) was used as basis.

Personal protection:

Please contact your supplier of equipment for personal protection for further guidance when choosing equipment for the working situation in question.

Respiratory protective equipment:

At concentrations higher than the occupational exposure limits, air-fed respiratory protective equipment should be used.

Hand protection:

Use disposable gloves of nitrile at risk of skin contact. In case of contact with the product change the glove immediately since the permeation rate of the glove towards solvents is very limited.

In case of repeated or prolonged contact with the product a 4H-glove should be used (permeation rate >4 hours).

Eye protection:

Use suitable eye protection if there is a risk of splashes.

Skin protection:

Work clothes.

9. Physical and chemical properties:

Physical state:	Liquid
Colour:	Yellow
Flash point:	< 21 °C
Density, g/ml:	0,9 (20 °C)
Water solubility:	Insoluble
Weight% organic solvents:	60-80
Product, Flammable liquid of class:	I-1

10. Stability and reactivity:

Stable under the recommended storage and handling conditions (see section 7).

If exposed to high temperatures, hazardous decomposition products may be produced (CO, CO₂, HCl).

Keep the product away from oxidising agents and strongly alkaline or acidic materials to prevent possibility of exothermic reaction.

11. Toxicological information: (Properties injurious to health)

Inhalation:

Exposure to organic solvent vapours may result in adverse health effects on several organs so as the renal and central nervous system. Poisoning symptoms include loss of memory and difficulties in concentration, fatigue, irritability and in extreme cases, loss of consciousness.

Skin contact:

Repeated or prolonged contact with the product may lead to removal of natural fats from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Eye contact:

Splashes in the eye may cause irritation.

Ingestion:

Ingestion by accident can cause vomiting and pain in the stomach. Chemical pleurisy may occur, if solvents come in the lungs at vomiting. Can cause damage of the kidney.

12. Ecological information:

Do not release product into the environment or the drains.

Xylen: LC50 Fish: *Pimephales promelas*/96 h: 21 mg/l
EC50 *Daphnia*/24: 310 mg/l
Degradability: Easy biodegradable (OECD-test 301C)
Is not bioaccumulated in the aquatic environment.

Ethyl acetate: LC50 Fish/96h: >200 mg/l
EC50 *Daphnia*/48h: 700 mg/l
Relatively readily biodegradable
Is not bioaccumulated in the aquatic environment (log Pow: 0,66)

Naphtha (petroleum), hydrotreated light: Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.

13. Disposal considerations:

Wastes incl. emptied containers are controlled wastes and should be disposed of in accordance with national or local regulations.

EWC-code: 08 04 09

14. Transport information:

Proper shipping name: Adhesives, containing a flammable liquid.

UN-nr.: 1133

ADR/RID: Class: 3 Pk.gr: II


IMDG: Class: 3 Pk.gr: II
EmS: F-E, S-D MP: -

ICAO/IATA: Class: 3 Pk.gr: II

15. Regulatory information:

This product has been classified in accordance with Danish and EC Directives on Hazardous Materials:

Hazard symbol:



Contains: Xylene. Colophony. May produce an allergic reaction.

R-phrases:

R20/21: Harmful by inhalation and in contact with skin.
R36/38: Irritating to eyes and skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

S-phrases:

S2: Keep out of reach of children.
S29: Do not empty into drains.
S37: Wear suitable gloves.
S46: If swallowed, seek medical advice immediately and show the container or label.

Application restrictions: In Denmark the product may not be used of youth under eighteen years old.

16. Other information:

Text of R-phrases listed in section 3

R10: Flammable
R11: Highly flammable
R20/21: Harmful by inhalation and in contact with skin.
R36: Irritating to eyes.
R38: Irritating to skin.
R43: May cause sensitisation by skin contact.
R48/20: Harmful: danger of serious damage to health by prolonged exposure through inhalation.
R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.
R66: Repeated exposure may cause skin dryness or cracking.
R67: Vapours may cause drowsiness and dizziness.

Compared to the last safety datasheet changes has been made in the sections: 1 and 8.

The information contained in this safety data sheet is based on the present state of knowledge and current EC and Danish legislation.

The product should not be used for purposes other than those shown in Section 1.

As the specific conditions of use of the product are outside the suppliers control, the user is responsible for ensuring that the requirements of relevant legislation are complied with.

The information in this safety data sheet provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitable for particular applications.

In case of medical attention, bring this safety data sheet.